

High Speed Centrifuge



Memory program



Stable rotation



Temperature protection function



Multi-rotor, big working capacity

TECHNICAL DATA

Model	MC-10Pro	MC-12Pro
Control Mode	Digital display & Button	
Max Relative Centrifugal Force	6708xg	9660xg
Speed Range	1000-10000rpm±5%	1000-12000rpm±5%
Rotor Capacity	0.2/0.5/1.5/2ml*12 + 0.2ml*8*4 Centrifuge tube 0.5/1.0ml*12 Micro blood tube Hematocrit rotor: 40mm*12 Capillary tube	
Max Speed Acceleration / Reduction	≤12 s/ ≤15s	
Noise Under Max Rotation Speed	≤47db (A)	
Input Power	48W	
Shell Protection Level	AC100-240V / DC24V	
Allow Surrounding Temperature	5 - 40 C / 80%RH	



High Speed Centrifuge



Memory program



Stable rotation



Temperature protection function



Enclosed high-speed type rotor

TECHNICAL DATA

Model	MC-13Pro	MC-15Pro
Control Mode	Digital display & Button	
Max Relative Centrifugal Force	11337xg	14104xg
Speed Range	1000-13000rpm±5%	1000-14500rpm±5%
Rotor Capacity	0.2/0.5/1.5/2ml*12 Centrifuge tube 0.5/1.0ml*12 Micro blood tube	
Max Speed Acceleration / Reduction	≤12 s/ ≤15s	
Noise Under Max Rotation Speed	≤47db (A)	
Input Power	50W	55W
Shell Protection Level	AC100-240V / DC24V	
Allow Surrounding Temperature	5 - 40 C / 80%RH	